## AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Compte 8 • CH-1844 Villeneuve • +41 (0)21 965 65 65

test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



## Flight test report: EN 926-2:2013+A1:2021\* and NfL 2-565-20

Manufacturer Davinci Products Inc		<b>).</b>	Certification num	nber	PG_2268.2023		
Address 53 sinchon-gil, Okchec 12505 Gyeonggi-do Korea, Republic of		on-myeon, `	Flight test		11.07.2024		
Glider model	POPERA XS		Classification		D		
Serial number	PPR-XS57013-LM		Representative		None		
Trimmer	no		Place of test		Villeneuve		
Folding lines used	yes						
Test pilot		Victor Chinen Cirilli			Alexandre Jofresa		
Harness		Advance Thun AG Success 4 M			Advance Thun AG Success 4 M		
Harness to risers di	istance [cm]	43		43			
Distance between risers [cm]		40		44			
Total weight in flight [kg]		75		95			
1. Inflation/Take-off		С					
Rising behaviour		Overshoots, shall be slowed down to avoid a front C collapse		Overshoots, shall be slowed down to avoid a from collapse	nt C		
Special take off technique required		No A		A	No	А	
2. Landing		А					
Special landing technique required		No		A	No	A	
3. Speed in straight fligh	3. Speed in straight flight						
Trim speed more than 30 km/h		Yes A		Yes	А		
Speed range using the controls larger than 10 km/h		Yes A		А	Yes	А	
Minimum speed		25 km/h to 30 km/h B		В	25 km/h to 30 km/h	В	
4. Control movement		С					
Max. weight in flight up to 80 kg							
Symmetric control pressure / travel		Increasing / 40 cm to	55 cm	С	not available	0	
Max. weight in flight 80 kg to 100 kg		not available		0	Increasing / 45 cm to 60 cm	С	
Symmetric control pressur				U		0	
Max. weight in flight greater than 100 kg Symmetric control pressure / travel		not available		0	not available	0	
5. Pitch stability exiting accelerated flight Dive forward angle on exit		A Dive forward less thar	n 30°	А	Dive forward less than 30°	А	
Collapse occurs		No A		A	No	A	
6. Pitch stability operating controls during accelerated flight		Α					
Collapse occurs		No		A	No	A	
7. Roll stability and damping		Α					
Oscillations		Reducing		A	Reducing	A	
8. Stability in gentle spirals		A					
Tendency to return to straight flight		Spontaneous exit		A	Spontaneous exit	A	

\*This standard is NOT covered by accreditation D-IS-19457-01

The validation of this test report is given by the signature of the test manager on inspection certificate 91.20 Rev 07 | 04.03.2022 // ISO | 91.22 // Page 1 of 5

9. Behaviour exiting a fully developed spiral dive	В			
Initial response of glider (first 180°)	No immediate reaction	В	No immediate reaction	В
Tendency to return to straight flight	Spontaneous exit (g force decreasing, rate of turn decreasing)	A	Spontaneous exit (g force decreasing, rate of turn decreasing)	A
Turn angle to recover normal flight	720° to 1 080°, spontaneous recovery	В	720° to 1 080°, spontaneous recovery	В
10. Symmetric front collapse Approximately 30 % chord	D			
Entry	Rocking back less than 45°		Rocking back less than 45°	А
Recovery	Spontaneous in less than 3 s		Spontaneous in less than 3 s	A
Dive forward angle on exit Change of course	Dive forward 0° to 30° / Keeping course		Dive forward 0° to 30° / Keeping course	А
Cascade occurs	No		No	A
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
At least 50% chord Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Recovery through pilot action in less than a further 3 s	D	Spontaneous in 3 s to 5 s	В
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	A	Dive forward 0° to 30° / Keeping course	А
Cascade occurs	not available	0	No	А
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
With accelerator				
Entry	Rocking back less than 45°	A	Rocking back less than 45°	A
Recovery	Recovery through pilot action in less than a further 3 s	D	Spontaneous in 3 s to 5 s	в
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	A	Dive forward 0° to 30° / Keeping course	A
Cascade occurs	No	A	No	А
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
11. Exiting deep stall (parachutal stall)	В			
Deep stall achieved	Yes		Yes	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 30° to 60°	В	Dive forward 0° to 30°	A
Change of course	not available	0	Changing course less than 45°	A
Cascade occurs	not available	0	No	A
<b>12. High angle of attack recovery</b> Recovery	A Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Cascade occurs	No	A	No	A
<b>13. Recovery from a developed full stall</b> Dive forward angle on exit	<b>C</b> Dive forward 60° to 90°	с	Dive forward 60° to 90°	С
Collapse	No collapse	A	No collapse	А
Cascade occurs (other than collapses)	No	A	Νο	A

Rocking back	Greater than 45°	С	Greater than 45°	С
Line tension	Most lines tight		Most lines tight	A
14. Asymmetric collapse	D			
Small asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	$90^\circ$ to $180^\circ$ / Dive or roll angle $15^\circ$ to $45^\circ$		$90^\circ$ to $180^\circ$ / Dive or roll angle $15^\circ$ to $45^\circ$	В
Re-inflation behaviour	Inflates in less than 3 s from start of pilot action		Inflates in less than 3 s from start of pilot action	С
Total change of course	Less than 360°		Less than 360°	A
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)		No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No		No	A
Cascade occurs	No	A	No	А
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	$90^\circ$ to $180^\circ$ / Dive or roll angle $45^\circ$ to $60^\circ$	С	$90^\circ$ to $180^\circ$ / Dive or roll angle $15^\circ$ to $45^\circ$	В
Re-inflation behaviour	Inflates in less than 3 s from start of pilot action	С	Inflates in less than 3 s from start of pilot action	С
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	A	No	A
Cascade occurs	No	A	No	A
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	$90^\circ$ to $180^\circ$ / Dive or roll angle $45^\circ$ to $60^\circ$	С	$90^\circ$ to $180^\circ$ / Dive or roll angle $15^\circ$ to $45^\circ$	В
Re-inflation behaviour	Inflates in less than 3 s from start of pilot action	С	Inflates in less than 3 s from start of pilot action	С
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	А
Twist occurs	No	A	No	А
Cascade occurs	No	A	No	A
Folding lines used	Yes (Only if asked)	D	Yes (Only if asked)	D
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	$180^\circ$ to $360^\circ$ / Dive or roll angle $45^\circ$ to $60^\circ$	С	$90^\circ$ to $180^\circ$ / Dive or roll angle $15^\circ$ to $45^\circ$	В
Re-inflation behaviour			Inflates in less than 3 s from start of pilot action	С
Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	A	No	A
Cascade occurs	No	A	No	A

Folding lines used	Yes (Only if asked)		Yes (Only if asked)	D
15. Directional control with a maintained	A			
asymmetric collapse Able to keep course	Yes	A	Yes	А
180° turn away from the collapsed side possible in 10 s	Yes	A	Yes	A
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	A	More than 50 % of the symmetric control travel	A
16. Trim speed spin tendency	Α			
Spin occurs	No	A	No	A
17. Low speed spin tendency Spin occurs	A No	A	No	A
18. Recovery from a developed spin	D			
Spin rotation angle after release	Stops spinning in 180° to 360°	D	Stops spinning in 180° to 360°	D
Cascade occurs	No	A	No	A
19. B-line stall	0			
Change of course before release	not available	0	not available	0
Behaviour before release	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit	not available	0	not available	0
Cascade occurs	not available	0	not available	0
20. Big ears	В			
Entry procedure	Standard technique	A	Standard technique	A
Behaviour during big ears	Stable flight	A	Stable flight	А
Recovery	Spontaneous in 3 s to 5 s	В	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
21. Big ears in accelerated flight	C			
Entry procedure	Standard technique	A	Standard technique	A
Behaviour during big ears	Unstable flight	С	Stable flight	А
Recovery	Recovery through pilot action in less than a further 3 s	В	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	А
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	A	Stable flight	А
22. Alternative means of directional control	Α			
180° turn achievable in 20 s	Yes	A	Yes	A
Stall or spin occurs	No	A	No	A
23. Any other flight procedure and/or configuration described in the user's manual	Α			
Procedure works as described	Yes	A	Yes	А
Procedure suitable for novice pilots	Yes	A	Yes	А
Cascade occurs	No	A	No	A

24. Comments of test pilot

Ears by B3